

Benefits:

- 40% Larger than yel-Low Safety Dolly
- Dolly Fits within Standard Doorways
- Move in Any Direction
- Move Multiple Objects, Different Sizes and Weights
- Base Model Dolly Can Carry Up to 1000 lbs
- Durable Welded Unibody Steel Construction

Standard Equipment:

- 12 Gauge Steel Unibody Box
- Four - 56" square 16 Gauge Posts
- Four 4" Polyurethane Over Cast Iron Casters
- Powder Coated Steel Unibody
- 1000 lb Weight Capacity
- E-Track Strap Access Positions (8)
- Low Loading Height, Lower than a Pallet
- Floor Clearance of 5/8"

Optional Accessories:

- Additional Posts in Various Lengths
- Dock Transition Wheels
- Brakes (set of 2)
- Corner Protectors/Connectors
- Fixed Direction Caster
- Forklift Posts
- Hi/Lo Caster Bracket Kit



Shuttle Dolly		*Optional Accessories
Product Specifications		
Material Construction	12 Gauge Steel Unibody	
Post Position Locations on Top of Dolly Body (Vertical)	12	
Overall Dimensions without Posts	36"L x 29"W x 5-1/4"H	
Overall Dimensions with Posts Installed (56" Posts Vertical)	36"L x 29"W x 57"H	
Dock Transition Wheel Material / Weight of 4 Assembly*	4" Solid Polypropylene/ 4.7lbs	
Maximum Capacity	1000 lbs	
Brakes - Weight Capacity (Set of 2) Assembly*	Brakes Rated 600 lbs Each Holding Capacity	
Deck Height	5-1/4"	
Floor Clearance	5/8"	
Casters - Total Number / Dock Transition Caster *	4 / 5	
Caster Size - Wheel Material	4" Polyurethane Over Cast Iron	
Caster - Type	Swivel	
Finish - Color	Powder Coat Yellow	
Weight - Without Posts / With (4) 56" Posts	70 lbs / 97 lbs	