

Job Site Scoop Dolly



Perfect for transporting items on the job site

Improve Job Site Productivity

A Job Site Version of our Scoop Dolly for All-Terrain Travel

The **Manual Job Site Scoop Dolly** is made of powder coated steel and aluminum angle construction. It uses a 68" pivoting support brace and a 4 position saddle post system to angle the product's center of gravity over the dolly, regardless of the product's height.

The Manual Job Site Scoop Dolly uses up to seven flat-free 10" tires in operation. With four locking, flat-free, pivoting tires and three flat-free fixed tires, it has an expanded footprint that allows it to go over gravel, rocks and mud.

The vertical posts can be used with E-track straps to hold the product to the dolly.



Base Model


Optional Accessories

Available for both Manual and Motorized Job Site Scoop Dollies.



Adjustable Backer Plate

Provides adjustable mounting for Drywall Lips. Ensures secure alignment & steadier handling.



Reinforced Drywall Lip

A reinforced version of the Standard Drywall Lip. Increases Drywall Lip weight capacity to 700 lbs.

BASE MODEL SPECIFICATIONS

- 1000 lbs. weight capacity
- 72"L x 32"W x 72"H (without outrigger support)
- 72"L x 48"W x 72"H (with outrigger support)
- (4) 10" locking swivel foam-filled tires
- (2) 10" locking fixed foam-filled tires
- Removable outrigger support with 10" fixed tire
- (4) 68" laser cut posts with E-track slots
- Weighs 328 lbs.



Manual Configuration shown on Jobsite and Loading Dock.

Trusted by Shops, Warehouses & Fabricators Nationwide.

www.sawtrax.com | 770-974-0021 | 888-SAWTRAX

