Raised Safety Dolly

An indoor/outdoor production dolly

Base Model

Configurable to Your Needs

Get 3-4x Employee Productivity with the Raised Safety Dolly

The Raised Safety Dolly gives the user the option of using the dolly outside with the wheels mounted to the corners. Locking casters are used with a bracket to support the fourth hole of the caster with the bottom of the decking.

GREAT FOR MOVING:

- Doors & Door Frames
- Large Panels
- Canopies & Awnings
- Windows & Glass Units
- Drywall & Sheet Goods
- Cabinets & Millwork

AND MORE!

BASE MODEL SPECIFICATIONS

- 1000 lbs. weight capacity
- 30"L x 25"W x 9 5/8"H (without posts)
- 30"L x 25"W x 61 3/8"H (with posts)
- Includes six 56" square 16 gauge posts
- 18 vertical/8 horizontal post positions
- Four 4" locking casters
- 12 Gauge steel unibody
- Weighs 83 lbs. (with six 56" posts)

OPTIONAL ACCESSORIES

- Shelf Plate
- Forklift Posts
- Forklift Channels (requires two Raised Safety Dolly Bodies)
- Fixed Direction Casters
- Dock Transition Wheels
- Rubber Finial Post Toppers
- Corner Protectors / Connectors
- Additional Posts in Various Lengths

Follow Us on Social Media! Scan QR for More Information.

www.sawtrax.com | 770-974-0021 | 888-SAWTRAX