

Raised Safety Dolly

An indoor/outdoor production dolly



Configurable to Your Needs

Get 3-4x Employee Productivity with the **Raised Safety Dolly**

The **Raised Safety Dolly** gives the user the option of using the dolly outside with the wheels mounted to the corners. Locking casters are used with a bracket to support the fourth hole of the caster with the bottom of the decking.



Base Model

GREAT FOR MOVING:

- Doors & Door Frames
- Large Panels
- Canopies & Awnings
- Windows & Glass Units
- Drywall & Sheet Goods
- Cabinets & Millwork

AND MORE!



BASE MODEL SPECIFICATIONS

- 1000 lbs. weight capacity
- 30"L x 25"W x 9 5/8"H (without posts)
- 30"L x 25"W x 61 3/8"H (with posts)
- Includes six 56" square 16 gauge posts
- 18 vertical/8 horizontal post positions
- Four 4" locking casters
- 12 Gauge steel unibody
- Weighs 83 lbs. (with six 56" posts)



OPTIONAL ACCESSORIES

- Shelf Plate
- Forklift Posts
- Forklift Channels (requires two Raised Safety Dolly Bodies)
- Fixed Direction Casters
- Dock Transition Wheels
- Rubber Finial Post Toppers
- Corner Protectors / Connectors
- Additional Posts in Various Lengths

Follow Us on Social Media! Scan QR for More Information.

www.sawtrax.com | 770-974-0021 | 888-SAWTRAX

